

## TPE Wallbox Power Dot



### Innovation

- LED screen with status display
- Modern design with smart control

### Smart control

- Wireless communication
- OCPP-communication protocol
- Smart charging or scheduled charging

### Safety

- 6mA DC leakage current detection
- Emergency stop

### Flexible option

- Type 2 charging cable or socket  
RFID-authorization or plug and play  
Wall-mounted or pile mounted

Specifications	Model	TPE Wallbow Power Dot
<b>Input</b>	Inlet	3P+N+PE
	Rated voltage	400V AC
	Rated current	16A/32A
	Frequency	50/60Hz
<b>Output</b>	Outlet voltage	400V AC
	Maximum current	16A/32A
	Rated power	11/22kW
<b>User display</b>	Charging cable	Type 2 cable
	Cable length	5m or 7.5m
	Interaction with the computer	LED screen
	LED indicator	Yes
	RFID reader	Yes
	Protection	Plug & Play / RFID
	Emergency stop	Yes
<b>Communication</b>	WLAN	Yes
	OCP	OCP 1.6 Jason
<b>Safety</b>	DC leakage current detection	6mA DC
	Protection type	IP54
	Certification	CE
	Electrical protection	Overcurrent protection, Lightning protection Over/under voltage protection Over/under temperature protection
	Regulations	EN 61851-1 & EN 61851-22
	Guaranty	2 years
<b>Environment</b>	Installation possibilities	Wall mounted / Pile mounted
	Standby power demand	2W
	Operational temperature	-30°C -+ 50°C
	Relative humidity	5%-95%
	Altitude	<2000m
<b>Package</b>	Product dimension	234*343*115m (H*W*D)
	Net weight	5,0 kg